# Shower Room Detachable Container House Modular Easy Deployment Quick Relocation

## **Basic Information**

- Place of Origin:
- Brand Name:
- Certification:
- Model Number:
- Minimum Order Quantity: 7 Sets
- Price:
- Packaging Details:
- Supply Ability:
- CE, ISO14001, ISO9001, ISO45001 D05
- USD 1200~1500/Set

China

7 units/20gp 17 units/40hq

**INFINITE STARS** 

2000 Sets PER Month



# **Product Specification**

- Type:
- Loading Quantity:
- Design:
- Wall Material:
- Dimensions:
- Structure:
- Port:
- Main Materia:
- MOQ:
- Highlight:
- Light Steel Structure Frame 7 Units/20gp 17 Units/40hq Based On Customer's Request Rock Wool Sandwich Panel 5950mm(L) \* 3000mm(W) \* 2800mm(H) Steel Structure Frame Welded Shanghai, Ningbo Port Light Steel Frame & Sandwich Panel 7 PCS
- Shower Room Detachable Container House, Detachable Container House Modular



### More Images



for more products please visit us on prefabricated-containerhouses.com

#### **Product Description**

#### Modular Shower Room Detachable Container House Easy Deployment Quick Relocation

Choosing detachable container house shower and toilet units offers many benefits, includes but not limits to below: Firstly, Easy to move: You can transport them easily, making them great for temporary setups like construction sites or outdoor events.

Secondly, Flexible: You can arrange them however you want because they're not fixed in place.

Additionally, Cost-effective: They're often cheaper than permanent structures, especially for short-term needs.

Moreover, Quick to install: Since they're pre-made, you can set them up quickly.

Furthermore, Clean and convenient: They come with modern amenities and are easy to keep clean.

Lastly, Environmentally friendly: Some are designed to be eco-friendly, reducing their impact on the environment.

	mentally mentally. 00	The are designed to be eee menuly, reducing their impac
Product Specification: 3-meter standard container	Length(mm)	5950(5730)
	Width(mm)	3000(2800)
	Height(mm)	2800(2500)
	Center column	
	Roof	Flat roof, free drainage
	Number of floors	≤3
Design parameters	Service life	5-8 years
	Ground live load	1.8KN/
	Roof live load	0.5KN/
	Wind load	0.6KN/
	Seismic degree	8
Structural	corner column	galvanized cold rolled section steel, t=2.3mm, material Q235B
	roof main beam	galvanized cold rolled section steel, t=2.3mm, material Q235B
	roof sub-beam	Galvanized square steel 5*5, t=1.5mm, radian galvanized square steel 4*6t= 1.2mm material Q235B
	floor main beam	galvanized cold-rolled section steel, t=2.3mm, material Q235B
	floor sub-beam	galvanized square steel 4*8 (5), galvanized square steel 8*8 (4) material Q235B
	Paint	Graphene Powder spraying (Electrostatic spraying)
Roof	Roof panel	0.40mm thick color steel plate, color white gray
	Ceiling	0.25mm thick 811 ceiling, color white gray
Floor	Decorative surface	
	basic floor	18mm sanding board
Wall	Thickness	50mm thick color steel glass fiber sandwich board; The outer and inner plates are made of 0.3mm aluminum plated zinc color steel plate
	Heat preservation	50mm thick glass silk wool, bulk weight ≥60kg/m³, combustion performance is class A non-combustible
	Color	white gray PE coating
	Spec(mm)	Width X height =920*2030 common door
1		

Door	Material	Steel door
Window	Spec(mm)	Front window: width X height =920*1200; Rear window (standard) : width X height =920*1200;
	Frame	Plastic steel window single glass
	Glass	common
Electricity	Voltage	220V~250V
	Wire	input power wire is 4 square, AC wire is 4 square, socket wire is 2.5 square, lighting switch wire is 1.5 square
	Circuit breaker	High break Miniature Circuit breaker (32A)
	Lamp tube	Two sets of circular LED fluorescent lamps
	Socket	3 five-hole socket 10A, 1 three-hole air conditioning socket 16A





